

## PRODUCT SPOTLIGHT

INNOFIT  
SERIES



**GREENCREATIVE**  
Bringing You the Latest in LED Technology



### Introducing the INNOFIT SERIES

Designed and engineered for retrofit or new construction installation, this downlight features adjustable lumen output for three distinct lumen levels equivalent to various CFL lamp combinations. The CDL is universally compatible in existing architectural and commercial housings and features easy-fit installation with adjustable spring-action housing clips. Simply install this retrofit solution and turn **ON** the savings.

- For retrofit or new construction installation
- ENERGY STAR certified
- Adjustable lumen output - 3 defined light levels
- Universally compatible with correct housings
- Easy-fit installation
- Universal voltage 120-277V
- Comfortable diffused light
- Soft / Warm / Neutral / Cool White CCT
- UL Listed & UL Classified

### CDL INNOFIT SERIES



9.5" CDL 45W



8" CDL 27W



6" CDL 21W



4" CDL 14W


# COMMERCIAL DOWNLIGHT PRODUCT FEATURES

## Adjustable Lumen Output

This commercial downlight features adjustable lumen output for three distinct lumen levels equivalent to various CFL lamp combinations. Simply adjust the lamp power to the desired lumen output by sliding the selector switch on top of the fixture.



Get a **FREE Energy Audit** to see how much your facility can save with the new **INNOCFIT** commercial downlight.



## SPECIFICATIONS\*

	Model	Product	CCT	Power (W)	Lumens (lm)	LPW	Beam Angle	CRI (typ.)	Dim	Life (hrs)	Voltage	
	45CDLA9.5/827/277V	57878	2700K	23.5/32/45	1860/2325/2975	79/73/66	110°	80	No	40,000	120-277V	Mar.
	45CDLA9.5/830/277V	57879	3000K	23.5/32/45	2000/2500/3200	85/78/71	110°	80	No	40,000	120-277V	Mar.
	45CDLA9.5/835/277V	57880	3500K	23.5/32/45	2000/2500/3200	85/78/71	110°	80	No	40,000	120-277V	Mar.
	45CDLA9.5/840/277V	57881	4000K	23.5/32/45	2000/2500/3200	85/78/71	110°	80	No	40,000	120-277V	Mar.
	27CDLA8/827/277V	57873	2700K	12/19/27	930/1400/1860	78/74/69	110°	80	No	40,000	120-277V	
	27CDLA8/830/277V	57874	3000K	12/19/27	1000/1500/2000	83/79/74	110°	80	No	40,000	120-277V	
	27CDLA8/835/277V	57875	3500K	12/19/27	1000/1500/2000	83/79/74	110°	80	No	40,000	120-277V	
	27CDLA8/840/277V	57876	4000K	12/19/27	1000/1500/2000	83/79/74	110°	80	No	40,000	120-277V	
	21CDLA6/827/277V	57868	2700K	8.5/13.5/21	650/930/1400	76/69/67	110°	80	No	40,000	120-277V	
	21CDLA6/830/277V	57869	3000K	8.5/13.5/21	700/1000/1500	82/74/71	110°	80	No	40,000	120-277V	
	21CDLA6/835/277V	57870	3500K	8.5/13.5/21	700/1000/1500	82/74/71	110°	80	No	40,000	120-277V	
	21CDLA6/840/277V	57871	4000K	8.5/13.5/21	700/1000/1500	82/74/71	110°	80	No	40,000	120-277V	
	14CDLA4/827/277V	57863	2700K	6/9/14	465/650/930	78/72/66	110°	80	No	40,000	120-277V	Mar.
	14CDLA4/830/277V	57864	3000K	6/9/14	500/700/1000	83/78/71	110°	80	No	40,000	120-277V	Mar.
	14CDLA4/835/277V	57865	3500K	6/9/14	500/700/1000	83/78/71	110°	80	No	40,000	120-277V	Mar.
	14CDLA4/840/277V	57866	4000K	6/9/14	500/700/1000	83/78/71	110°	80	No	40,000	120-277V	Mar.

\* Specification data is preliminary and may be subject to change  
 \*\* Suitable for damp locations